

# SANAN SA-1110P



<b>Image Sensor</b>	PIXIM 1/3 Seawolf Solution
<b>Lens</b>	(Optional)
<b>OSD</b>	OSD Menu

<b>Model</b>		<b>SA-1110P</b>
<b>Image Sensor</b>		PIXIM 1/3 Seawolf Solution
<b>TV System</b>		PAL/NTSC
<b>Horizontal Resolution</b>		690 HTVL-E
<b>Mini.Illumination</b>		0.1 Lux (IR ON)
<b>S/N Ratio</b>		≥50dB (AGC OFF)
<b>WDR Control</b>		Medium,normal,low,high
<b>BLC</b>		ON,OFF
<b>AGC</b>		Normal,low,high
<b>White Balance</b>	<b>Mode</b>	Automatic Tracking White,Balance(ATM)
	<b>Automatic</b>	(Auto White Balance) 2200~10000K°
<b>Day/Night</b>		OFF, External Control,Auto; ON
<b>Synchronous mode</b>		Internal synchronous
<b>Lens</b>		(Optional)
<b>Sens-Up</b>		1-32 times
<b>WDR</b>		120dB (max)

<b>Noise Reduction</b>		3D Motion Adaptive
<b>Power</b>	<b>Voltage</b>	DC 12V/ AC 24V
	<b>Current</b>	<150mA
<b>Lens Interface</b>		CS
<b>Video Out</b>		1.0Vp-p/75 $\Omega$
<b>Operating Environment</b>		-10°C ~ +50°C
<b>Dimension(mm)</b>		127×60×52mm
<b>Weight</b>		400g