

SANAN SA-1346



Optional Models

SA-1346

520TVL 1/3" SONY SUPER HAD CCD、LED 18PCS、IR Distance 12m、D1、0.5Lux、H.264 Main Profile、Dual-Stream、SD Card;

Optional Lens

Optional Lens: 6mm/8mm/12mm Lens(6mm Best Results 5-10M,8mm Best Results 10-20M,12mm Best Results 20-30M)

Features

* 1/3" SONY SUPER HAD CCD;

* Digital high definition upto 704x576;

* Support color to black at day and night

* Built-in focal iris lens , 6mm/8mm/12mm(optional)

*18pcs IR LEDs,IR distance is 12m

*Support H.264/MJPEG video compression ,dual-streaming,high compression ratio and high quality recording

* Support Auto white balance

* High **S/N Ratio**

* Support local voice picked-up ,two way audio

*SDHC Card supports video storage and image snapping; SD2.0 standard, maximum storage 16G(Optional)

* Mmulti-protocol ,Ethernet/WiFi/3G

* Support 4 areas mask setting,protect user's privacy.
* Support Motion detection,network fault detection ,alarm recording, snap pictures.
* Built-in Web Server,IE browser , parameter configuration ,update,user authority .
* Power supply: DC 12V/1A

Model	SA-1346	
Type	IP Dome Camera	
SoC Chip	HISILICON HI3512	
Sensor Model	1/3" SONY SUPER HAD CCD, 520TVL	
Total pixels	0.3 million pixels	
Minimal Illumination	0.1Lux(Color)@F1.2; 0.01Lux(B/W)@F1.2(IR ON 0Lux with IR)	
Day&Night	Supports	
IR Parameters	18 PCS IR LEDs, IR distance 12m	
Electronic Shutter	1/50-1/10,000sec	
Lens	Fixed Iris,6mm fixed Iris lens, 8mm/12mm(Optional)	
Audio Talkback	1 Channel MIC input	
Audio Output	1 Channel linear Output	
Storage Interface	SDHC Card supports video storage and image snapping; SD2.0 standard, maximum storage 16G(Optional)	
Network Interface	LAN	10/100M BASE-TX,RJ-45 Connector
I/O	1 Channel input, Normally Open/Normally Close Modes adjustable; 1 channel output, 120VAC 1A/24VDC 1A, 1 RS485 interface	
Video Compression	H.264 Main Profile MJPEG/JPEG Baseline	
Resolution (Dual Streaming)	D1:704×576(PAL),25f/s;704×480(NTSC),30f/s Half-D1:704×288(PAL), 25f/s;704×240(NTSC),30f/s CIF:352×288(PAL), 25f/s;352×240(NTSC),30f/s CIF:176×144(PAL), 25f/s;176×120(NTSC),30f/s	
Video Bitrate	32Kbps~16Mbps, Supports CBR/VBR	
Title OSD	Supports channel name, date, and video stream information overlay; OSD location is adjustable	
Audio Compression	G.726	
Recording	Recording set up to record by motion trigger, alarm trigger, manual, or schedule	
Alarm Output	E-mail, Explorer, Software	
Network Protocol	TCP/IP, UDP, RTP, RTSP, RTCP, HTTP, DNS, DDNS, DHCP, FTP, NTP, PPPOE, SMTP, UPNP	
Remote View	Computer	IE 6.0 or up, max 10 user
	Mobile Phone	Windows Mobile, Symbian, Iphone
Working Temperature	-10°C ~ +55°C	

Working Humidity	0%-90%
Power Supply	DC 12V
Power Consumption	7W(MAX)
Dimension(mm)	132mm×105mm
N.W(g)	390g