

## SANAN SA-1508B



* Image Sensor	1/3" SONY Color CCD;
* Resolution	420TVL, 540TVL(Optional);
* Lens	2.8-10mm Manual Varifocal lens;
* LED	∅ 5mm×35PCS;
* IR Distance	30-40m;
* Bracket	All-Oriented Bracket With Cable Conceal Inside;
* Waterproof	IP66;
* OSD	OSD Menu option for multi-function;
* Optional Color	White.

Model	SA-1508B SH	SA-1508B S	SA-1508B HW	SA-1508B H
Image Sensor	1/3" SONY	1/4" SONY	1/3" SHARP	1/4" SHARP
TV System	PAL/NTSC			
Effective Pixel	PAL:752(H)×582(V) NTSC:768(H)×494(V)		PAL:500(H)×582(V) NTSC:510(H)×492(V)	
Horizontal Resolution	540TVL		420TVL	
Minimal Illumination	0.000Lux×F1.2(LED On)			
Synchronous System	Internal Synchronization			
S/N Ratio	≥48dB			
Electronic Shutter	1/50-1/100,000s(PAL) 1/60-1/100,000s(NTSC)			
BLC	No			
Day/Night	Yes			

<b>LED</b>	∅ 5mm×35PCS
<b>IR Distance</b>	30-40m
<b>Waterproof</b>	IP66
<b>Power Supply</b>	DC 12V±10% 800mA
<b>Working Temperature</b>	-20°C~+50°C RH95% Max-
<b>Storage Temperature</b>	-20°C~+60°C RH95% Max-
<b>Dimension(mm)</b>	80mm×160mm×264mm
<b>Weight(g)</b>	927g