

# SANAN SA-1523P



<b>Image Sensor</b>	PIXIM 1/3 Seawolf Solution
<b>Lens</b>	8-20mm Auto Iris Lens
<b>LED</b>	∅ 5mm×56PCS
<b>IR Distance</b>	60m
<b>OSD</b>	OSD Menu
<b>Waterproof</b>	IP66 Weather-Proof
<b>Other</b>	IR-CUT

<b>Model</b>		<b>SA-1523P</b>
<b>Image Sensor</b>		PIXIM 1/3 Seawolf Solution
<b>Horizontal Resolution</b>		690 HTVL-E
<b>Mini.Illumination</b>		0Lux (IR ON)
<b>S/N Ratio</b>		≥50dB (AGC OFF)
<b>WDR Control</b>		Medium,normal,low,high
<b>BLC</b>		ON,OFF
<b>AGC</b>		Normal,low,high
<b>White Balance</b>	<b>Mode</b>	Automatic Tracking White Balance (ATW)
	<b>Automatic</b>	(Auto White Balance) 2200~10000K°
<b>Day/Night</b>		OFF, External Control,Auto; ON
<b>Synchronous mode</b>		Internal synchronous
<b>Lens</b>		8-20mm Auto Iris Lens
<b>LED</b>		∅ 5mm×56PCS

<b>IR Distance</b>		60m
<b>IR CUT</b>		Auto Switchover
<b>Sens-Up</b>		1-32 times
<b>WDR</b>		120dB (max)
<b>Noise Reduction</b>		3D Motion Adaptive
<b>Power</b>	<b>Voltage</b>	DC 12V/ AC 24V
	<b>Current</b>	<750mA
<b>Operating Environment</b>		-10°C ~ +50°C
<b>Dimension(mm)</b>		275×85×110mm
<b>Weight</b>		1400g