

SANAN SA-1564



* Image Sensor	1/3" SONY SUPER HAD CCD;
* Resolution	420TVL/540TVL/600TVL(Optional);
* Lens	3.5-8mm Vari-focal Lens;
* LED	48PCS;
* IR Distance	30-40m;
* Waterproof	IP65.

Model	SA-1564		
Image Sensor	1/3" SONY SUPER HAD CCD		
TV System	PAL/NTSC		
Effective Pixel	PAL:500(H)×582(V) NTSC:510(H)×492(V)	PAL:752(H)×582(V) NTSC:768(H)×494(V)	PAL:795(H)×596(V) NTSC:811(H)×508(V)
Horizontal Resolution	420TVL	540TVL	600TVL
Minimal Illumination	0Lux/F1.4 (IR LED On)		
Synchronous System	Internal Synchronization		
S/N Ratio	>52dB		
Electronic Shutter	1/50-1/100,000s(PAL) 1/60-1/100,000s(NTSC)		
BLC	Auto		
AGC	Auto		
Gamma Adjusting	>0.45		
Video Output	1.0 Vp-p Composite Output (75Ω/BNC)		
Control Mode	Manual Focus		

Lens	3.5-8mm Vari-focal Lens
LED	48 PCS 850nm Infrared LED
IR Distance	30-40m
LED life	20,000hrs, Warranty life: 6,000hrs
Angle Of View	102°~45°
Waterproof	IP65
Power Supply	DC 12V(+/-10%) Max.1500mA/ Max.18W
Working Temperature	-20°C~+50°C RH≤90%
Storage Temperature	-20°C~+60°C RH≤90%
Dimension(mm)	280mm×225mm×135mm
Weight(g)	2000g