

SANAN SA-1816



* Image Sensor	1/3" SONY CCD;
* Resolution	420TVL~700TVL(Optional);
* Lens	4-9mm Manual Zoom Lens(2.8-10mm Lens Optional);
* Bracket	3 Axis Bracket;
* Other	2.5" Vadal-proof Dome Camera.

Model	SA-1816		
Image Sensor	1/3" Sony CCD		
TV System	PAL/NTSC		
Effective Pixel	PAL:500(H)×582(V) NTSC:510(H)×492(V)	PAL:752(H)×582(V) NTSC:768(H)×494(V)	PAL:795(H)×596(V) NTSC:811(H)×508(V)
Horizontal Resolution	420TVL	540TVL	600TVL
Minimal Illumination	0.1Lux/F1.2 0Lux(IR On)		0.001Lux/F1.2 0Lux(IR on)
Synchronous System	Internal Synchronization		
S/N Ratio	>48dB	>54dB	
Electronic Shutter	1/50-1/60,000s(PAL) 1/60-1/60,000s(NTSC)		
White Balance	ATW		
BLC	On		
AGC	Auto		
Gamma Adjusting	0.45		

Video Output	1.0Vp-p at 75Ω
Lens	4-9mm Manual Zoom Lens(2.8-10mm Lens Optional)
Power Supply	DC 12V
Working Temperature	-10°C~+50°C RH90% MAX
Dimension(mm)	210mm×100mm
Weight(g)	780g